



6		5		4		3		2		1		
FILE: 2016-D02\ULO								REV	E.C.N NO.	CONTENT	CHK	DATE
								V0.0		初做	ZCP	17.01.04

NOTES:

- Rating: <UL> 300V/10A  
<IEC> 250V/10.5A
- Poles:02-24P
- Insulation Withstands Voltage: AC2000V/1 Min
- Insulation Resistance: 500MΩ at DC500V
- Using Temperature Range: -40°C/+115°C
- Suitable Electric Wire:16-28AWG(UL),0.2-1.5mm<sup>2</sup>(IEC);
- Max soldering : +250° for 5S
- RoHS Compliance.
- With "★" is import dimension

How to order

**ULO-TB12 - 235/5.0 - XXP -Y 0 0 0A**

Certificate Series NO.      Factory Code      poles      color:      Customer requirements

1:Grey  
2:Blue  
3:Black  
4:Green  
5:Orange  
6:Red  
7:transparent  
8:Yellow  
9:White

**P.C.B LAYOUT**

Total Pitch Tolerances in mm										Nominal dimension range in mm										⊥	≡	—	//		
over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 10	all	over 0	over 100	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5		

5	SPRING COIL	X00000200	N	STAINLESS	/
4	LEVER	3003D0YXXA	N	PA66	UL94V-0
3	SOLDERPIN	3002B0010	N	Phosphor Bronze	Tin Plated
2	Cover	3002C0YXXA	1	PA66	UL94V-0
1	Housing	3002A0YXXA	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	ZCP	DATE	17.01.04	UNITS	MM
CHK.		DATE		SCALE	1:1
APP.		DATE			
				NAME	<b>ULO-TB12-235/5.0-XXP-Y000A</b>
				NAME	宁波欧路电子有限公司
				DWG NO.	ULOTB12Y000A