



CPC-2101

21.5" Intel® Celeron® Processor POI System

- Intel® Celeron® Processor N3160 (2M Cache, up to 2.24 GHz)
- 21.5" LCD 1920x1080 FHD Display with PCAP touch
- 2 x 204-pin DDR3L 1600 MHz SO-DIMM supports up to 8GB Max (Default: 1 x 2GB DDR3L)
- 1 x 2.5" Storage
- 4 x USB 3.0, 2 x USB 2.0, 3 x COM
- 2 x Intel® i211AT Gigabit Ethernet
- Fanless System & VESA Compliance
- 12V 5A 60W Adapter

+ Spec

System	
Processor	Intel® Celeron® Processor N3160 (2M Cache, up to 2.24 GHz)
System Memory	2GB DDR3L SO-DIMM
SBC	EMX-BSWP
Expansion	
Expansion	1 x Mini PCI-e for 802.11B/G/N WiFi Module
Storage	
Storage	1 x 2.5" Storage 1 x Mini PCI-e supports mSATA
I/O	
USB	2 x USB 2.0 4 x USB 3.0
COM Port	2 x RS232 1 x RS232/422/485
HDMI	1 x HDMI
VGA	1 x VGA
Audio	
Chipset	Realtek ALC662
Audio Interface	Mic-In, Line-Out and S/PDIF
Audio Amplifier	2 x 3W
Ethernet	
Chipset	2 x Intel® i211AT Gigabit Ethernet
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45
Mechanical & Environmental	
Operating Temp	0°C ~ 40°C (32°F ~ 104°F)
Storage Temp	-10°C ~ 50°C (14°F ~ 122°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Dimension (L x W)	528 x 345 x 62 mm
Weight	9.48 kg
System Fan	Fanless
Construction - Front	Black Coverlens
Construction - Rear	White
Power Requirement	
Power Connector	DC Jack
Power Requirement	+12V
Power Mode	ATX
Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A)
Panel	
LCD Size	21.5", 16:9
Display Type	Full HD
Resolution	1920 x 1080
Luminance	250nits
Contrast ratio	3000
Viewing angle	(H) 178, (V) 178
Backlight	LED
Data Collection	
Camera	1 x 1.0M Pixels Webcam

+ Ordering

CPC-2101-A1R
21.5" Panel PC with Intel® Celeron® Processor N3160 / 2GB DRAM / 60W Adapter

