


Suggested P.C.B Layout

技术参数/Specifications	
额定参数/Rating	0.1A 12VDC
环境温度/Environment Temperature	-25℃ ~ 85℃
接触电阻 Contact Resistance	≤ 50mΩ
绝缘电阻/Insulation Resistance	≥ 100MΩ (at 500VDC)
耐电压 Withstand Voltage	100V AC/10mA/5s
电气寿命 Electrical life	500V AC/10mA/5s
操作力 Operating force	100000 Cycles
	260 ± 50gf

电气原理图:
CIRCUIT:



NOTE:
TOLERANCE UNLESS OTHERWISE SPECIFIED
X. ± 0.30 . X ± 0.20 . XX ± 0.10

修改日期/修改内容 MODIFY DATE/CONTENT	
审核日期/审核人 CHECK DATE/PERSON	
设计日期/设计 DESIGN DATE	
制图日期/制图 DRAWING DATE	
零件号 PART NO.	
图号 DRAWING FILE NO.	
图名 DRAWING FILE NO.	
日期 DATE	

成品图 PRODUCT DRAWING		浙江佳龙电子有限公司 ZHEJIANG JIALONG ELECTRON CO., LTD	
图号 DRAWING NO.	图名 DRAWING NAME	比例 SCALE	轻触开关 Tact Switch
设计 DESIGN	审核 CHECK	重量 WT.	
制图 DRAWING	日期 DATE	数量 QTY.	
工艺 TECHNOLOGY		图幅 SIZE	11-TC-06F