

REV	DESCRIPTION	DESIGN	DATE
A0	Release		2016.06.27

Circuits	Dimensions (mm)			Circuits	Dimensions (mm)		
	DIM. A	DIM. B	DIM. C		DIM. A	DIM. B	DIM. C
02	2.50	5.60	8.00	08	17.50	20.60	23.00
03	5.00	8.10	10.50	09	20.00	23.10	25.50
04	7.50	10.60	13.00	10	22.50	25.60	28.00
05	10.00	13.10	15.50	11	25.00	28.10	30.50
06	12.50	15.60	18.00	12	27.50	30.60	33.00
07	15.00	18.10	20.50				

**Main Specifications**  
 Poles : 02 to 12  
 Contact resistance :  $\leq 20\text{m}\Omega$   
 Insulation resistance :  $\geq 500\text{M}\Omega$   
 Rated voltage : 250V AC DC  
 Rated current : 3.0A AC DC  
 Withstand voltage : 1500V AC/minute  
 Temperature Range : -25°C --- +85°C



C					
B					
A	PEDESTAL		1 PCS	PA66	
ITEM	COMPONENT		Q'TY	MATERIAL	FINISH
<b>LEDsconn</b>					TITLE: -
X. $\pm 0.5$	X. $\pm 5^*$	USE: CUSTOMER		PART NO.:	
.X $\pm 0.3$	.X $\pm 2^*$	APPD:		DWG NO.:	
.XX $\pm 0.25$	.XX $\pm 1^*$	CHKD:		SCALE	
--	--	DR:		1 : 1	SHEET
		UNITS: mm			1 / 1

