



MSBP2111LMC 21" Medical Display

- > IP65 in front & IPx1 whole unit
- > ALS (optional)
- > Calibration mode(optional)
- > 20 meter DV/HDMI long cable solution



+ Spec

| Panel | |
|----------------------------------|--|
| LCD Size | 21.5" |
| Display Type | Full HD |
| Resolution | 1920 x 1080 |
| Luminance | 230 Cd/m2 |
| Contrast ratio | 1000:1 |
| Viewing angle | 89/89 Deg. Horizontal & Vertical |
| Backlight | LED |
| Touch Type | Projective Capacitive |
| AG Protection Glass | Yes |
| DICOM compliant | Yes |
| I/O | |
| RS232 | Optional |
| Input Interface | 1 x VGA 1 x DVI 1 x HDMI 1 x Display Port |
| Mechanical & Environmental | |
| Power Type | 24V DC In |
| Operating Temperature | 0°C ~ 40°C (32°F ~ 104°F) |
| Storage Temperature | -20°C ~ 60°C (-4°F ~ 140°F) |
| Operating Humidity | 10%~90% Relative Humidity, Non-condensing |
| Weight | 5.5 Kgs |
| Construction | Plastic |
| Mounting Kit | Stand (Optional) VESA Mount kit (Optional) Wall Mount kit (Optional) |
| Vibration Test | With SSD/mSATA: 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis |
| Shock Test | With SSD/mSATA: 10Grms, IEC 60068-2-27, Half Sine, 11ms |
| System Fan | Fanless |
| Dimension | 521.07 x 326.07 x 56.5 mm |
| Certifications | |
| Certification Information | CE(EN60601-1) FCC certified cTUVus certified |

+ Ordering

G2MSBP211LMC2120
MSBP2111LMC with AG Glass 230nits
21.5"/LED/AG Glass/1920x1080/Plastic Case/230nits/1000 contrast/
VGA/DV/HDMI/DP
DVI cablex1/VGA cablex1/Delta 90W Adapter
NO: Power Cord

G2MSBP211LMC1120
MSBP2111LMC with AG PCAP 220nits
21.5"/LED/AG PCAP/1920x1080/Plastic Case/210nits/1000 contrast/
VGA/DV/HDMI/DP
DVI cablex1/VGA cablex1/Delta 90W Adapter
NO: Power Cord