

DC Fan**40x40x28 mm****San Ace 40 9GA** type Low Power Consumption Fan**General Specifications**

- Material Frame: Plastic (Flammability: UL 94V-0), Impeller: Plastic (Flammability: UL 94V-0)
- Expected life See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60°C, rated voltage) Expected life at 40°C is for reference only.
- Motor protection function Locked rotor burnout protection, Reverse polarity protection
For details, please refer to p. 599.
- Dielectric strength 50/60 Hz, 500 VAC, for 1 minute (between lead wire conductors and frame)
- Insulation resistance 10 MΩ or more with a 500 VDC megger (between lead wire conductors and frame)
- Sound pressure level (SPL) At 1 m away from the air inlet
- Storage temperature -30 to +70°C (Non-condensing)
- Lead wire Red Black Sensor Yellow Control Brown
- Mass 53 g

Specifications

The models listed below have ribs and pulse sensors with PWM control function. For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	PWM duty cycle [%]	Rated current [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min] [CFM]	Max. static pressure [Pa] [inch H₂O]	SPL [dB (A)]	Operating temperature [°C]	Expected life [h]
② 9GA0412P3K01	12	10.8 to 13.2	100	0.92	11.04	22000	0.81 28.6	799 3.21	61	-20 to +60	30000/60°C (53000/40°C)
			0	0.1	1.2	6500	0.23 8.12	68 0.27	32		
② 9GA0412P3J01	12	10.8 to 13.2	100	0.49	5.88	18000	0.67 23.7	535 2.15	54	-20 to +70	40000/60°C (70000/40°C)
			0	0.05	0.6	4500	0.16 5.7	33 0.13	22		
② 9GA0412P3G01	12	10.8 to 13.2	100	0.39	4.68	16500	0.61 21.5	450 1.81	53	-20 to +70	40000/60°C (70000/40°C)
			0	0.05	0.6	4500	0.16 5.7	33 0.13	22		
② 9GA0412P3H01	12	10.8 to 13.2	100	0.28	3.36	14500	0.54 19.1	347 1.39	50	-20 to +70	40000/60°C (70000/40°C)
			0	0.04	0.48	3500	0.13 4.6	20 0.08	17		
② 9GA0412P3M01	12	10.8 to 13.2	100	0.21	2.52	12500	0.46 16.2	258 1.04	47	-20 to +70	40000/60°C (70000/40°C)
			0	0.04	0.48	3500	0.13 4.6	20 0.08	17		
② 9GA0424P3J001	24	21.6 to 26.4	100	0.27	6.48	18000	0.67 23.7	535 2.15	54	-20 to +70	40000/60°C (70000/40°C)
② 9GA0424P3G001			100	0.22	5.28	16500	0.61 21.5	450 1.81	53		
② 9GA0424P3H001			100	0.16	3.84	14500	0.54 19.1	347 1.39	50		
② 9GA0424P3M001			100	0.11	2.64	12500	0.46 16.2	258 1.04	47		


* PWM input frequency is 25 kHz; models without specifications at 0% PWM duty cycle have zero fan speed at 0%.

Note 1: Sensor and control options are available for selection. Refer to the table on p. 628.


Note 2: The ② mark indicates Short LeadTime Service applicable models. See p. 654 for details.

Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example**9GA0412P3K01** With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9GA0412P3J01 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9GA0412P3G01 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9GA0412P3H01 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9GA0412P3M01 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9GA0424P3J001 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9GA0424P3G001 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9GA0424P3H001 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9GA0424P3M001 With pulse sensor with PWM control function


PWM duty cycle





Operating voltage range



PWM duty - Speed characteristics example



Dimensions (unit: mm) (With ribs)**Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)****Options**

Finger guards

page: p. 584

Model no.: 109-059, 109-059H