



NOTES1:

- 1.Rating voltage/current: 450V/24A
- 2.wire range: 0.75-2.5mm²sol

NOTES2:

- 1.Housing: PC
- 2.Conductor: Brass
- 3.Spring:Stainless Steel

NOTES3:

- 1.Stripping length: 12mm
- 2.Operating temperature: -20°C ~ +105°C

How to order
 ULO - PC-252

Certificate Factory
 Series NO. Code

Total Pitch Tolerances in mm										Nominal dimension range in mm										⊥	≡	-	//								
over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 10	over 100	over 150	0	10	all	0	0.3	0.2	0.3	0.5
to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 30	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 10	to 10	to 100	to 150	to 150	0.2	0.3	0.3	0.2	0.3	0.3	0.5	
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.2	0.3	0.3	0.2	0.3	0.5		

ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE
DWG.	CKK	DATE	21.11.04	UNITS	MM
CHK.		DATE		SCALE	1:1
APP.		DATE		SHEET/OF	A4
				NAME	ULO-PC-252
				DWGNO.	UL0Y000A