

# Shenzhen Top Power Co.,Ltd.

Add:3/F.,Bldg.B5,Junfeng Industrial Park,Yonghe Road,Heping,Fuyong,Shenzhen

Tel:+86-755-23359172 29919580 Fax:+86-755-29919580

<http://www.sz-toppower.com>

Contact:Henry Email:henry@sz-toppower.com Skype:toppower.henry

## 24w eu catalogue

| Item | Description   | Photo   |
|------|---|---|
| 1    | <p>Model Name: <b>TPS-0503000EU(5V 3A), TPS-0504000EU(5V 4A), TPS-0603000EU(6V 3A), TPS-0902000EU(9V 2A), TPS-1201500EU(12V 1.5A), TPS-1202000EU(12V 2A), TPS-1501500EU(15V 1.5A), TPS-1801000EU(18V 1A), TPS-2400750EU(24V 0.75A), TPS-2401000EU(24V 1A)</b></p> <p>Rated Output Power: 24W Max.<br/>Output Voltage &amp; Current : 5Vdc-24Vdc, 0.01A-4A<br/>AC plug: <b>EU 2pin plug</b><br/>Dimension : 71.8*43*31.5 (mm)<br/>Certification: <b>GS,CE,ROHS</b><br/>Efficiency: Level V<br/>Input Voltage: 100-240Vac<br/>Variation Range: 90-264Vac<br/>Load Regulation: <math>V_{out} \pm V_{out} * 5\%</math><br/>Ripple And Noise(Max.): no more than 120mVp-p<br/>Turn On Delay Time: 3 second Max. At 230VAC<br/>Rise Time: 100mS Max. At 230Vac<br/>Hold Up Time: 7mS Min. At 230Vac<br/>Protection: OTP/OCP/OVP/SCP<br/>Operating Temperature: 0℃ to 40℃,Full load, Normal<br/>Storage Temperature: -20℃ to 85℃<br/>Relative Humidity: 5%(0℃)~90%(40℃)RH,72Hrs,Full load, Normal operating<br/>Vibration: Operating: IEC 721-3-3 3M3/IEC 721-3-2 2M2/Axes,10 cycles per axis/Dropping tests: 1 corner,3 edges, and 6 surfaces one time for each surface<br/>(DIELECTRIC STRENGTH)(Hi-Pot): (Primary to secondary),3000Vac/10mA/1Min.<br/>Surge immunity with 1K voltage</p> |  |

### Remark:

- 1 The DC cable length can be 1.2m, 1.5m, 1.8m, 2.0m, 2.5m, 3.0m.
- 2 DC plug size can be 5.5\*2.1\*10 or 5.5\*2.5\*10 (mm).
- 3 Price will be calculated based on your specific details requirements.
- 4 Payment terms: 30% T/T as deposite,70% T/T before loading!
- 5 Lead time: 35-40days after get the deposite!