



■ SPECIFICATIONS

- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,000V AC/minute
- Insulation Resistance : 1,000MΩ min.
- Temperature Range : - 40°C to + 105°C
- Contact Resistance : 20mΩ max.

■ HOUSING

- Part No. : JS-1105X-XXx2
- △ Plastic:
 - Blank: Noryl
 - A: PBT

- Poles : 04~80
- Material : High Temp. Plastic
- Mating Wafer : JS-1106-XXx2
JS-1106-XXx2(6T)
JS-1107-XXx2
- Mating Terminal : JS-1105-T
- Q' ty : 1,000 Pcs/Tube Packing

Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
4	2.54	5.08	44	53.34	55.88
6	5.08	7.62	46	55.88	58.42
8	7.62	10.16	48	58.42	60.96
10	10.16	12.70	50	60.96	63.50
12	12.70	15.24	52	63.50	66.04
14	15.24	17.78	54	66.04	68.58
16	17.78	20.32	56	68.58	71.12
18	20.32	22.86	58	71.12	73.66
20	22.86	25.40	60	73.66	76.20
22	25.40	27.94	62	76.20	78.74
24	27.94	30.48	64	78.74	81.28
26	30.48	33.02	66	81.28	83.82
28	33.02	35.56	68	83.82	86.36
30	35.56	38.10	70	86.36	88.90
32	38.10	40.64	72	88.90	91.44
34	40.64	43.18	74	91.44	93.98
36	43.18	45.72	76	93.98	96.52
38	45.72	48.26	78	96.52	99.06
40	48.26	50.80	80	99.06	101.60
42	50.80	53.34			



喬訊電子工業股份有限公司

CHYAO SHIUNN
ELECTRONIC INDUSTRIAL LTD.

PART NO JS-1105X-XXx2

2.54mm Center Mini Latch Housing

APPROVED BY

張育瑞

CHECKED BY

黃科源

DRAWN BY

王誠賢

SCALE

PROJ

DATE



2010/07/20

UNIT

mm

VER NO.

a6

SIZE

A4

TOLERANCE

.0 ±0.3

.00 ±0.2

.000 ±0.1

ALL ±

ANGLE

0° ±

.0° ±

LTR

△

△

△

△

△

△

REVISION RECORD

REVISION RECORD	DATE
材質修改	06/03/29
材質修改	07/07/04
材質修改	08/06/04
將缺角補齊	10/05/19
料號修正並新增PBT塑膠材質	10/07/21

Conforms to The RoHS Instruction CUSTOMER