



# KBU/RS 4A/6A/8A SERIES

<p><b>SINGLE PHASE 4.0/6.0/8.0AMPS. SILICON BRIDGE RECTIFIERS</b></p>	<p><b>Voltage Range 50 to 1000 Volts Current 4.0/6.0/8.0 Amperes</b></p>
<p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>● Surge overload rating - 200 ~ 300 amperes peak</li> <li>● Ideal for printed circuit board</li> <li>● Reliable low cost construction utilizing molded plastic technique</li> <li>● Mounting Position: Any</li> <li>● Mounting Torque: 5 In.lb.Max.</li> </ul>	<p style="text-align: center;">Dimensions in inches and (millimeters)</p>

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Rating at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 50Hz, resistive or inductive load.  
For capacitive load, derate current by 20%

	Type Number	KBU4005	KBU401	KBU402	KBU404	KBU406	KBU408	KBU410	UNITS
		KBU6005	KBU601	KBU602	KBU604	KBU606	KBU608	KBU610	
		KBU8005	KBU801	KBU802	KBU804	KBU806	KBU808	KBU810	
Maximum Repetitive Peak Reverse Voltage	VRRM	50	100	200	400	600	800	1000	V
Maximum RMS Bridge Voltage	VRMS	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	VDC	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current at Tc=100°C, TA=50°C/40°C/45°C	IF(AV)		4.0 4.0			6.0 6.0		8.0 6.0	A
Peak Forward Surge Current, 8.3ms single half sine-wave super imposed on rated load (JEDEC Method)	IFSM		200	KBU6 RS6		250	KBU8 RS8	300	A
Maximum Instantaneous Forward Voltage Drop Per Leg at 2.0A/3.0A/4.0A	VF		1.0			1.0		1.0	V
Maximum Reverse Leakage at rated DC Blocking Voltage Per Leg TA=25°C TC=100°C	IR		10 1			10 1		10 1	µA mA
Operating and Storage Temperature Range	TJ,TSTG	-55 to +150							°C

## RATING AND CHARACTERISTIC CURVES KBU/RS 4A/6A/8A SERIES

