



## EAX-C246BP

Intel® 8/9th Gen. Core™  
i7/i5/i3/Pentium®/Celeron®/Xeon® E-2200/2100  
Processor ATX Motherboard With Intel® C246  
Chipset

- > Intel® 8/9th Generation Core™ i7/i5/i3/ Pentium®/ Celeron®/ Xeon® E-2200/2100 Processor
- > Intel® C246 Chipset
- > 4 x 288-pin DDR4 2400/2666MHz DIMM socket, supports up to 128GB (ECC memory support by CPU)
- > DVI-I, DP++, DP++, 4 x SATA III
- > 2 x PCI-e x16 slot for 1 x PCI-e x16 or 2 x PCI-e x8 (By Auto switch IC), 3 x PCI-e x4, 1 x PCI
- > 3 x USB 2.0 by pin header, 1 x USB 2.0 Vertical type A, 4 x USB 3.1 GEN 1 by pin headers (using PCI-e to USB 3.1 GEN 1 by BOM option)
- > PS/2 KB/MS + 2 x USB 3.1 Gen 2, 2 x RJ-45 with Dual deck for 4 x USB 3.1 GEN 2 connector, 4 x USB 3.1 GEN 1 connector at I/O
- > 1 x COM at I/O; 8 x RS232, 2 x RS232/422/485 (COM2 & 3 by BIOS selection)
- > Support RAID 0, 1, 5, 10
- > Onboard Infineon SLB9665 support TPM 2.0
- > ATX Power

### + Spec

#### -System Information-

<b>Processor</b>	Intel® LGA1151 Socket Supports 8/9th Generation Core™ i7/ i5/ i3 & / Intel® Xeon®Process(Workstation) / Pentium®/Celeron® Processors
<b>Platform Controller Hub</b>	Intel® C246 Chipset
<b>System Memory</b>	4 x 288-pin DDR4 2400/2666MHz DIMM supports up to 128GB (ECC memory supported by CPU)
<b>I/O Chipset</b>	Nuvoton® NCT6106D
<b>BIOS Information</b>	AMI uEFI BIOS, 256Mbit SPI Flash ROM
<b>Watchdog Timer</b>	H/W Reset, 5~255 seconds/5~255 minutes
<b>H/W Status Monitor</b>	CPU temperature monitoring, Voltages monitoring, CPU fan speed control
<b>TPM</b>	Onboard Infineon SLB9665 supports TPM 2.0
<b>Board</b>	ATX Board

#### Expansion

<b>Expansion</b>	1 x PCI 2 x PCI-e x16 slot for 1 x PCI-e x16 or 2 x PCI-e x8(By Auto switch IC) 3 x PCI-e x4
------------------	--

#### I/O

<b>USB Port</b>	PS/2 KB/MS + 2 x USB 3.1 GEN 2 2 x RJ-45 with Dual deck for 4 x USB 3.1 GEN 2 connector 4 x USB 3.1 GEN 1
<b>COM Port</b>	1 x COM
<b>SATA</b>	4 x SATA III
<b>DIO</b>	1 x 16-bit GPIO
<b>MIO</b>	1 x PS/2 Keyboard or 1 x PS/2 Mouse
<b>RS232</b>	8 x RS232 2 x RS232/422/485 (COM2 & 3 by BIOS selection)

#### Display

<b>Graphic Chipset</b>	Intel® 8/9th Generation CPU integrated
<b>Spec. &amp; Resolution</b>	DVI-I: 1920 x 1080 @ 60Hz DP++: 4096 x 2304 @ 60Hz
<b>Multiple Display</b>	Triple Display

#### Audio

<b>Audio Codec</b>	Realtek ALC888S
<b>Audio Interface</b>	Mic-in, Line-out by pin-header
<b>Audio Amplifier</b>	6W Amplifier

#### Ethernet

<b>LAN Chipset</b>	1 x Intel® I219LM Gigabit Ethernet PHY 1 x Intel® I210AT PCI-e Gigabit Ethernet
<b>LAN Port</b>	2 x RJ-45

#### Mechanical & Environmental

<b>Operating Temperature</b>	0~60°C (32~140°F)
<b>Storage Temperature</b>	-40 ~ 75°C
<b>Operating Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing
<b>Weight</b>	1.32lbs (0.6 kg)
<b>Power Requirement</b>	+12V/+5V/5VSB/+3.3V/-12V
<b>ACPI</b>	Single power ATX Support S0, S3, S4, S5
<b>Power Mode</b>	AT/ATX



<b>Dimension (L x W)</b>	12" x 9.6" (304.8mm x 243.84mm)
<b>Ordering Information</b>	
<b>Ordering Information</b>	EAX-C246BP-B1R Intel® LGA1151 Socket Supports 8th Generation Core™ i7/i5/i3 & / Intel® Xeon® Process(Workstation) / Pentium®/Celeron® Processors ATX Motherboard with Intel® C246 Chipset