

FOR .205 (.52) × .025 (.64) STANDARD BLADE FUSES

For Littelfuse ATOF 287 series/Bussmann ATC series or equivalent

- Holds fuse securely, even after multiple insertions
- Thru hole-mount, maintains position during wave soldering
- Withstands the rigors of shock and vibration
- Holder design prevents solder wicking

VERTICAL FUSE ENTRY

SPECIFICATIONS

Contacts: .016 (.41) Brass, Tin-Nickel Plate


Insulator: Glass filled Nylon, UL Rated 94V-0

UL Current Rating: 20 Amps @ 500V AC


UL Temperature Rating: -58°F to +292°F (-50°C to +145°C)




3522-2




Mounting Detail For Two Clips



3522-3



Mounting Detail For Two Clips



CAT. NO. 3522-2

CAT. NO. 3522-3


VERTICAL ENTRY

SPECIFICATIONS

Contacts: .016 (.41) Brass


UL Current Rating: 30 Amps @ 500 VAC

Mounting Detail For Two Clips



CAT. NO. 3522 Tin-Nickel Plate

LOW INSERTION FORCE



CAT. NO. 3573 Matte Tin Plate

2 IN 1 FUSE HOLDER

For Littelfuse ATOF 287 series/Bussmann ATC series, Littelfuse Low Profile Mini (LP) series or equivalents

- Low insertion force
- Fuse holder fully insulates clips to protect fuse from shorting
- Holder assures proper spacing and reduces assembly time
- Thru hole PC mountable, maintains position during wave soldering

SPECIFICATIONS


Contacts: .016 (.41) Brass, Tin-Nickel Plate

Insulator: Nylon 4/6, UL Rated 94V-0

UL Current Rating: 30 Amps @ 500V AC

UL Temperature Rating: -58°F to +292°F (-50°C to +145°C)


Mounting Detail



UNIVERSAL CLIP




For Littelfuse ATOF 287 series/Bussmann ATC series, Littelfuse Mini 297 or 997 series/Bussmann ATM series, Littelfuse Low Profile Mini (LP) series or equivalents

- Accepts most Auto-Blade Fuses
- Low insertion force
- Thru hole PC mountable, maintains position during wave soldering



CAT. NO. 3557 - Top Entry

CAT. NO. 3577 - Bottom Entry



CAT. NO.	COLOR	FUSE REF.
3557-2	Black	-
3557-10	Red	10 Amp
3557-15	Blue	15 Amp
3557-20	Yellow	20 Amp

All colors UL rated for 30 Amp.

HORIZONTAL FUSE ENTRY

- Designed for low height clearance applications
- Fuse will be inserted parallel to board
- Thru hole mount, maintains position during wave soldering
- Fuse holder fully insulates clips to protect fuse from shorting
- Holder assures proper spacing and reduces assembly time
- Polarized legs assure proper orientation of clips onto board


SPECIFICATIONS

Contacts: .012 (.30) Brass

Insulator: Nylon, UL Rated 94V-0

UL Temperature Rating: -58°F to +292°F (-50°C to +145°C)

Mounting Detail For Two Clips



CAT. NO. 3550-2 Tin Plate

UL Current Rating: 20 Amps @ 500V AC

UL Current Rating: 30 Amps @ 500V AC

CAT. NO. 3550 Tin-Nickel Plate

