



APC-15WR2

15.6" Applied Panel PC

- > RockChip RK3568 Cortex-A55, Quad Core up to 2.0GHz
- > 2GB / 4GB RAM, 32GB eMMC
- > PCAP Touch
- > 10/100/1000 Ethernet
- > RJ-45 for (RS232 or RS485)
- > DC 12~24V Input or Powered LAN 802.3at
- > 2.0MP Camera w/ D-Mic
- > Speaker 4Ω 2.0W/2.5W(MAX)
- > LED Light Bar
- > 75 x 75mm VESA Mount
- > Plastic has Antibacterial
- > Optional NFC Reader
- > Optional Handset

+ Spec

-System Information-	
Processor	RockChip RK3568 Cortex-A55, Quad Core up to 2.0GHz
System Memory	2GB/4GB LPDDR4 RAM
Storage	
Storage	32GB eMMC
Panel	
LCD Size	15.6"
Resolution	1920x1080
Luminance	400
Viewing angle	170°(H/V)
Touch Type	PCAP
I/O	
External I/O Connector	1 x RJ45 for RS232 or RS485 2 x USB 2.0 Type A 1 x 10/100/1000 Ethernet 1 x 4-Pin 3.5mm Audio Jack
Camera	2.0MP Camera
Data Collection	
Camera	2M pixel
NFC	NFC Reader
Wireless Communication	
WLAN	802.11ac/a/b/g/n
Bluetooth	BT 5.0
Display	
Spec. & Resolution	eDP: Max. resolution 1920x1280 @ 60Hz
Audio	
Speaker Output	4Ω 2.0W/2.5W(MAX)
Certifications	
Certification Information	CE, FCC Class B
Ethernet	
LAN Chipset	Realtek RTL8211F-CG
LAN Port	1 x RJ45
Power Requirement	
DC Input	Input: 100~240 Vac/50~60 Hz Output: 60W Adapter (12V @ 5A Adapter)
Mechanical & Environmental	
Operating Temperature	0°C ~ 40°C
Storage Temperature	-10°C ~ 60°C
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	2.4 kg
VESA	75 x 75
Dimensions(W x L x D)	388.5 x 26.3 x 31.5mm
Power Requirement	DC Input, 12~24V
Power Mode	DC jack or Powered LAN 802.3AT
Software Support	
OS Information	Android 11
Ordering Information	
Ordering Information	APC-15WR2-6803-A1R_15.6" RK3568, 2GB RAM, 32GB eMMC, 12~24V / Powered LAN, Android 11 APC-15WR2-6809-A1R_15.6" RK3568, 4GB RAM, 32GB eMMC, 12~24V / Powered LAN, Android 11