



IEC-3367

Digital Signage Player with Intel® 11th Core / Celeron® Processor



Features

- Intel® 11th Core / Celeron® Processor (Tiger lake-UP3)
- Dual DDR4 SODIMM sockets
- Dual HDMI output supported
- Dual GbE RJ45 ports
- 3 x RS-232, 6 x USB 3.0 ports
- 1 x M.2 2280 M-Key slot, 1 x M.2 2230 E-Key slot
- 1 x M.2 3052 B-Key slot

System

| | |
|-------------|---|
| CPU | Soldered onboard Intel® 11th Generation Core i7/ i5/i3 or Celeron® processor (Tiger Lake-UP3) |
| Memory | 2 x 260-pin DDR4 SO-DIMM socket, supporting 3200MHz SDRAM up to 64GB |
| Graphics | Integrated Intel® Iris® Xe / UHD Graphic (depends on CPU SKU) |
| LAN Chipset | 2 x Intel GbE RJ45 |

I/O

| | |
|---------------|--|
| Serial Port | 3 x DB-9 male connector for RS-232 |
| USB Port | 6 x USB 3.0 ports |
| LAN | 2 x RJ-45 ports for GbE |
| Video Port | 2 x HDMI max resolution up to 4096*2160@30Hz |
| Audio | 1 x Phone jack connector for Line-Out + MIC |
| Expansion Bus | 1 x M.2 2230 E-Key slot 1 x M.2 3052 B-Key slot |

Storage

| | |
|---------|--|
| Storage | 1 x M.2 2280 M-Key slot for PCIe x4 NVMe 1 x SATA 3.0 port for 2.5" SSD |
|---------|--|

Environmental

| | |
|--------------------|--|
| Operating Temp. | 0 ~ 40°C (32 ~ 104°F), ambient w/ air flow |
| Storage Temp. | -40 ~ 85°C (-40 ~ 185°F) |
| Operating Humidity | 10 ~ 95% @ 60°C (non-condensing) |
| Vibration | 1.0 Grms, IEC 60068-2-64, random, 5 ~500 Hz, 1 Oct./min, 1 hr/axis, operatio |
| Shock | Operating 10G, Non-operating 20G |

Qualification

| | |
|---------------|---------|
| Certification | CE, FCC |
|---------------|---------|

Power Requirement

| | |
|-------------------|-----------------------------------|
| Power Input | DC 12V input |
| Power Consumption | 1.28A @12V (typical w/ i7-1165G7) |

Mechanical

| | |
|------------------------|---|
| Construction | Aluminum alloy |
| Weight | 1.21KG |
| Dimensions (W x D x H) | 198.5 x 124 x 68.7 mm (7.82" x 4.89" x 2.71") |

OS Support


| | |
|--------------|--|
| Windows 10 | |
| Linux Ubuntu | |

Ordering Information







| | |
|-----------------|---|
| IEC-3367-1135G7 | Intel® Core i5-1135G7 Processor, 2 HDMI, 2 GbE, 6 USB, 3 RS-232, 8GB SDRAM, 256GB M.2 SSD |
|-----------------|---|

OEM Request

| | |
|-----------------|---|
| IEC-3367-1165G7 | Intel® Core i7-1165G7 Processor, 2 HDMI, 2 GbE, 6 USB, 3 RS-232 |
| IEC-3367-1115G4 | Intel® Core i3-1115G4 Processor, 2 HDMI, 2 GbE, 6 USB, 3 RS-232 |
| IEC-3367-6305E | Intel® Celeron 6305E Processor, 2 HDMI, 2 GbE, 6 USB, 3 RS-232 |



Dimensions



Unit: mm

Standard Accessories

Power Adaptor 12VDC, 5A, 60W, 2.5φ JACK, AC/DC Adaptor with power cord



Optional Configuration (CTOS* Kit)

4GB SO-DIMM DDR4-2666 4GB SO-DIMM Memory module

8GB SO-DIMM DDR4-2666 8GB SO-DIMM Memory module

16GB SO-DIMM DDR4-2666 16GB SO-DIMM Memory module

256GB SSD 256GB M.2 2280 SSD PCIe Gen3x4

512GB SSD 512GB M.2 2280 SSD PCIe Gen3x4

1TB SSD 1TB M.2 2280 SSD PCIe Gen3x4



*CTOS means *Configure-to-Order Service*.