



POSITION	A	B
10	22.36	10.16
14	27.44	15.24
16	29.98	17.78
20	35.06	22.86
26	42.68	30.48
34	52.84	40.64
40	60.46	48.26
44	65.54	53.34
50	73.16	60.96
56	80.78	68.58
60	85.86	73.66
62	88.40	76.20
64	90.94	78.74

SPECIFICATIONS

Material
 Insulator: FBT, glass reinforced, rated UL 94V-0
 Contact: Phosphor Bronze or Brass
Electrical
 Current Rating: 1 Amp
 Contact Resistance: 30 mΩ max.
 Insulation Resistance: 3000 MΩ min.
 Dielectric Withstanding Voltage: 500V AC for 1 minute
 Operating Temperature: -40°C to +105°C
 † Terminated with 1.27mm pitch flat ribbon cable.

UNLESS OTHERWISE SPECIFIED TOLERANCE
.X ± 0.3
.XX ± 0.2
.XXX ± 0.1

宏茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

制表日: 2004/02/04
 DRAWING. APPROVED
Kevin

UNIT	SCALE	PART NAME
MM		2.54mm EDGE CARD IDC TYPE W/O NOSE
APPD.	CKD.	PART NO.
		C2900-XXXXXXB00R
DRAWING. APPROVED	TOLERANCE	REV.
<i>Kevin</i>	± 0.1	A