



■ SPECIFICATIONS

- Voltage Rating : 100V AC/DC
- Current Rating : 2A AC/DC
- Withstanding Voltage : 800V AC/minute
- Insulation Resistance : 1,000M Ω min
- Temperature Range : - 25°C to + 85°C
- Contact resistance : 20m Ω max

■ WAFER

- Part No. : JS-1125R-XXX  
 JS-1125R-XX : GP Produces  
 JS-1125R-0XX : Non GP Produces
- Poles : 2-16
- Material : Contact : Brass, Tin Plated  
 Base : Nylon 66 UL94V-0
- Q' ty : 1,000 pcs/Bag

Poles	Part No.	Dimensions (mm)		
		A	B	C
2	JS-1125R-02	2.00	6.00	5.00
3	JS-1125R-03	4.00	8.00	7.00
4	JS-1125R-04	6.00	10.00	9.00
5	JS-1125R-05	8.00	12.00	11.00
6	JS-1125R-06	10.00	14.00	13.00
7	JS-1125R-07	12.00	16.00	15.00
8	JS-1125R-08	14.00	18.00	17.00
9	JS-1125R-09	16.00	20.00	19.00
10	JS-1125R-10	18.00	22.00	21.00
11	JS-1125R-11	20.00	24.00	23.00
12	JS-1125R-12	22.00	26.00	25.00
13	JS-1125R-13	24.00	28.00	27.00
14	JS-1125R-14	26.00	30.00	29.00
15	JS-1125R-15	28.00	32.00	31.00
16	JS-1125R-16	30.00	34.00	33.00

oznaczenie MARITEX: WS-XXR



喬訊電子工業股份有限公司  
 CHYAO SHIUNN  
 ELECTRONIC INDUSTRIAL LTD.

PART NO JS-1125R-XX  
 2.00mm Crimp Style Connectors Wafer

APPROVED BY	SCALE	UNIT	TOLERANCE	
林陳鏞	4:1	mm	.0	±0.3
CHECKED BY	PROJ	VER NO.	.00	±0.2
林勇生			.000	±0.1
DRAWN BY	DATE	SIZE	ALL	±
邱森鴻	2004/12/31	A4	ANGLE	
			0°	±
			.0°	±

LTR	REVISION RECORD	DATE