



REV	E.C.N NO.	CONTENT	CHK	DATE
V0.0		初版	ZCP	16.11.14

- NOTES:
- Rating: 300V/16A
<IEC> 320V/20A
 - Poles: 02-24P
 - Insulation Withstands Voltage: AC2000V/1 Min
 - Contact resistance: 20mΩ
 - Insulation Resistance: 500MΩ at DC500V
 - Using Temperature Range: -40°C/+115°C
 - Max soldering : +250° for 5S
 - RoHS Compliance.
 - With "★" "is important dimension"

How to order

ULO-TB27 - 2VC/5.08 - □□P -Y 000A

Certificate Series NO. Factory Code poles color: Customer requirements (standard)

- 1: Grey
- 2: Blue
- 3: Black
- 4: Green
- 5: Orange
- 6: Red
- 7: transparent
- 8: Yellow
- 9: White

Total Pitch Tolerances in mm										Nominal dimension range in mm										⊥	≡	-	//		
over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 10	all	over 0	over 100	over 150
to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 320	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 320	to 10	to 10	to 10	to 100	to 100	to 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	±0.90	±0.90	0.2	0.3	0.3	0.2	0.3	0.5

2	Solde pin	1002B0010	N	BRASS	Sn Plated
1	Housing	1006A0YXXA	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	ZCP	DATE	2016.11.14	UNITS	MM
CHK.		DATE		SCALE	1:1
APP.		DATE			
			NAME	ULO-TB27-2VC/5.08-XXP-Y000A	
			DWGNO.	UL0TB27Y000A	