



■ SPECIFICATIONS

- Voltage Rating : 250 V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,000V AC/minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max

■ TERMINAL

- Part No. : JS-1142-T, JS-1142-T(G) : GP Produces
  - Tin Plated
    - G:Gold Plated 1u"
    - G1:Gold Plated 15u"
    - G2:Gold Plated 30u"
    - G3:Gold Plated 3u"
- Applicable Wires : AWG# 22 - 30
- Material : Phos. Bronze
- Finish : Tin Plated, Gold Plated(Gold Flash)
- Thickness : 0.2mm
- Q' ty : 1,5000 pcs./Reel


 喬訊電子工業股份有限公司  
 CHYAO SHIUNN  
 ELECTRONIC INDUSTRIAL LTD.

PART NO JS-1142-T;JS-1142-T(G)  
 2.54mm Crimp Style Connectors Terminal

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
林宗	6:1	mm	.0 ±0.3	ECR	DG 200608-004	06/08/15			
CHECKED BY	PROJ	VER NO.	.00 ±0.2	ECR	DG 200611-003	06/11/09			
			.000 ±0.1	ECR	DG 200707-005	07/07/09			
		α3	ALL ±				CUSTOMER		
DRAWN BY	DATE	SIZE	ANGLE						
簡海平	2007/07/09	A4	0° ±						
			.0° ±						Conforms to The RoHS Instruction