



## FPC-17L08

17" 4th Gen Intel®Core™ Processor i7/i5/i3 All-in-One Multifunctional Touch Panel PC

- > 17" SXGA TFT Touch Panel PC
- > 5-wire Resistive Touch Screen
- > Supports 4th Gen Intel®Core™ i7/i5/i3 PGA Processor
- > VGA, DP, HDMI, Audio
- > Gigabit Ethernet, WiFi Module
- > 3 x COM, 5 x USB
- > 2.5" SATA HDD/SSD Support
- > IP65 Compliant Front Panel
- > VESA Compliance

### + Spec

System	
<b>Processor</b>	4th Gen Intel® Core™ i3-4330TE 2-Core 2.4GHz processor 4th Gen Intel® Core™ i5-4570TE 2-Core 2.7GHz processor
<b>System Chipset</b>	Intel® Q87 Chipset
<b>System Memory</b>	2 x 204-Pin DDR3 1333MHz SO-DIMM up to 16 GB
<b>I/O Chip</b>	Nuvoton NTC6106D
<b>SBC</b>	EMX-Q87
Expansion	
<b>Expansion</b>	1 x Mini PCIe Supports mSATA
Storage	
<b>Storage</b>	1 x 2.5" Drive Bay
I/O	
<b>USB</b>	4 x USB 3.0 1 x USB 2.0
<b>COM Port</b>	1 x RS-232/422/485 2 x RS-232
<b>Other</b>	1 x WiFi
Display	
<b>Chipset</b>	Intel® Q87 Chipset Integrated Supports triple display
<b>Resolution</b>	DP:Max. resolution 1920x1200 VGA:Max. resolution 2048x1536 HDMI:Max. resolution 1920x1200
Audio	
<b>Chipset</b>	Realtek ALC892 supports 5.1-CH
<b>Audio Interface</b>	Mic-In, Line-In and Line-Out
<b>Speaker Output</b>	2 x 2W
Ethernet	
<b>Chipset</b>	1 x Intel® I211AT 1 x Intel® I217LM
<b>Ethernet Interface</b>	10/100/1000 Base-Tx GbE compatible
<b>LAN Port</b>	2 x RJ-45
Mechanical & Environmental	
<b>Operating Temp</b>	0°C ~ 40°C (32°F ~ 104°F)
<b>Storage Temp</b>	-10°C ~ 50°C (14°F ~ 122°F)
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing
<b>Weight</b>	6.14Kgs
<b>Dimension (L x W x H)</b>	387.5 x 346 x 76.6 mm
<b>Vibration Test</b>	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
<b>Shock Test</b>	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
<b>System Fan</b>	Fan
<b>Construction - Front</b>	Black
<b>Construction - Rear</b>	Black
Certifications	
<b>Certification Information</b>	CE / FCC Class B
Software Support	
<b>OS Information</b>	Win 7 Win 8
Power Requirement	



<b>ACPI</b>	Single Power ATX Support S0, S1, S3, S4, S5 ACPI 3.0 Compliant
<b>Power Mode</b>	AT/ATX (ATX is default setting)
<b>Panel</b>	
<b>LCD Size</b>	17", 4:3
<b>Display Type</b>	SXGA
<b>Resolution</b>	1280 x 1024
<b>Pixel pitch</b>	0.264mm (H) x 0.264mm (V)
<b>Luminance</b>	350 cd/m2
<b>Contrast ratio</b>	800
<b>Viewing angle</b>	80 (U), 80 (D), 85 (L), 85 (R)
<b>Response time</b>	30 ms
<b>Backlight</b>	LED
<b>Touch Type</b>	5 Wires resistive
<b>Touch Light Transmission</b>	80 %
<b>Touch Controller</b>	USB touch (EETI)

### + Ordering

FPC-17L08-TH413-2R  
17" SXGA i3-4330TE 2.4GHz/4GR/32GSDD

ACC-FPC-WALLMT-03R  
Wall Mount Bracket Kit for FPC-17~21W B1

ACC-FPC-WALLMT-04R  
Openframe Bracket Kit for FPC-17 Series B1

ACC-ARM-D23R  
VESA Stand, 75 & 100mm