


RZ Low Impedance Series



- Low impedance at high frequency
- High reliability withstanding 5000 hours load life at 105°C (2000/3000 hours for smaller case sizes as specified below)
- Ideally suited for use in switching power supplies
- Complied to the RoHS directive


RZ → **RP**
Long life



Item	Characteristics												
Operating temperature range	-55 ~ +105°C												
Leakage current max.	$I = 0.01\text{CV}$ or $3\mu\text{A}$ whichever is greater (after 2 minutes) $I = 0.03\text{CV}$ or $4\mu\text{A}$ whichever is greater (after 1 minute)												
Capacitance tolerance	$\pm 20\%$ at 120Hz, 20°C												
Dissipation factor max. (at 120Hz, 20°C)	Capacitance $> 1000\mu\text{F}$: $\tan\delta$ increases by 0.02 for each $1000\mu\text{F}$ from below value												
	WV	6.3	10	16	25	35	50	63					
	$\tan\delta$	0.22	0.19	0.16	0.14	0.12	0.10	0.08					
Low temperature characteristics (Impedance ratio at 120Hz)	WV	6.3, 10		16 ~ 35		50, 63							
	Z-55°C/Z+20°C	4		3		2							
Load life	After an application of DC bias voltage plus the rated AC ripple current for 5000 hours at 105°C. The measurement shall meet the following limits. The DC voltage plus the peak AC voltage combined must not exceed the rated voltage.												
	Leakage current	Less than specified value											
	Capacitance change	Within $\pm 20\%$ of initial value											
	$\tan\delta$	Less than 200% of specified value											
	$\emptyset D$	$\emptyset D \leq 6.3$		$\emptyset D = 8$		$\emptyset D \geq 10$							
	Life time	2000 hours		3000 hours		5000 hours							
Shelf life (at 105°C)	After 1000 hours no load test, leakage current, capacitance and $\tan\delta$ are same as load life value. The measurement shall be performed at 20°C by the KS C IEC 60384 - 4												
	Leakage current	Less than specified value											
	Capacitance change	Within $\pm 20\%$ of initial value											
	$\tan\delta$	Less than 150% of specified value											

DRAWING

Unit : mm



$\emptyset D$	5	6.3	8	10	12.5	16	18
P	2.0	2.5	3.5	5.0	5.0	7.5	7.5
$\emptyset d$	0.5	0.5	0.6	0.6	0.6	0.8	0.8
β	1.5		2.0				

FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

μF	Frequency	120Hz	1kHz	10kHz	50kHz	100kHz \leq
~ 33		0.40	0.65	0.82	0.91	1.00
47 ~ 270		0.50	0.70	0.84	0.92	1.00
330 ~ 680		0.55	0.75	0.86	0.93	1.00
1000 ~ 1500		0.60	0.80	0.88	0.94	1.00
2200 ~		0.70	0.85	0.90	0.95	1.00

MINIATURE ALUMINUM ELECTROLYTIC CAPACITORS

RZ series

● DIMENSIONS & MAXIMUM PERMISSIBLE RIPPLE CURRENT

WV μF	6.3				10				16				25			
	ØD × L (mm)	Impedance (Ω)max. 20°C 100kHz	Ripple current (mA rms) 105°C 100kHz	ØD × L (mm)	Impedance (Ω)max. 20°C 100kHz	Ripple current (mA rms) 105°C 100kHz	ØD × L (mm)	Impedance (Ω)max. 20°C 100kHz	Ripple current (mA rms) 105°C 100kHz	ØD × L (mm)	Impedance (Ω)max. 20°C 100kHz	Ripple current (mA rms) 105°C 100kHz	ØD × L (mm)	Impedance (Ω)max. 20°C 100kHz	Ripple current (mA rms) 105°C 100kHz	
33														5×11	0.80	155
47									5×11	0.80	155	6.3×11	0.55		210	
68				5×11	0.80	155	6.3×11	0.50	220	6.3×11	0.36		260			
100	5×11	0.85	150	6.3×11	0.55	210	6.3×11	0.35	265	8×11.5	0.24		383			
150	6.3×11	0.49	225	6.3×11	0.35	265	8×11.5	0.23	388	8×11.5	0.16		460			
220	6.3×11	0.30	285	8×11.5	0.24	387	8×11.5	0.16	460	10×12.5	0.13		600			
330	8×11.5	0.20	292	8×11.5	0.16	460	10×12.5	0.12	625	10×16	0.095		750			
470	10×12.5	0.14	575	10×12.5	0.13	600	10×16	0.09	770	10×20	0.065		1020			
680	10×16	0.11	700	10×16	0.09	770	10×20	0.065	1020	12.5×20	0.046		1392			
1000	10×20	0.075	950	10×20	0.060	1060	12.5×20	0.047	1411	12.5×25	0.036		1660			
1500	10×25	0.055	1220	12.5×20	0.045	1417	12.5×25	0.036	1660	16×20	0.034		1770			
2200	12.5×20	0.043	1438	12.5×25	0.034	1710	16×20	0.033	1800	16×25	0.028		2051			
3300	12.5×25	0.034	1710	16×20	0.031	1850	16×25	0.027	2095	16×35.5	0.020		2680			
4700	16×25	0.032	1935	16×31.5	0.023	2420	16×35.5	0.020	2680	18×40	0.018		2960			
6800	16×31.5	0.024	2370	16×35.5	0.020	2680	18×35.5	0.018	2900							
10000	16×40	0.020	2750	18×40	0.017	3040										
15000	18×40	0.018	2960													

WV μF	35				50				63			
	ØD × L (mm)	Impedance (Ω)max. 20°C 100kHz	Ripple current (mA rms) 105°C 100kHz	ØD × L (mm)	Impedance (Ω)max. 20°C 100kHz	Ripple current (mA rms) 105°C 100kHz	ØD × L (mm)	Impedance (Ω)max. 20°C 100kHz	Ripple current (mA rms) 105°C 100kHz	ØD × L (mm)	Impedance (Ω)max. 20°C 100kHz	Ripple current (mA rms) 105°C 100kHz
1.0				5×11	4.00	36						
1.5				5×11	3.80	45						
2.2				5×11	3.50	54						
3.3				5×11	3.00	66						
4.7				5×11	2.20	81						
6.8				5×11	1.80	91						
10				5×11	1.80	115	5×11	1.80	135			
15				5×11	1.60	145	6.3×11	1.00	185			
22	5×11	0.75	160	6.3×11	1.40	195	6.3×11	1.00	215			
33	6.3×11	0.49	225	6.3×11	1.20	240	8×11.5	0.80	320			
47	6.3×11	0.34	270	8×11.5	0.80	344	8×11.5	0.80	365			
68	8×11.5	0.24	384	8×11.5	0.65	410	10×12.5	0.23	495			
100	8×11.5	0.16	460	10×16	0.40	581	10×20	0.16	750			
150	10×12.5	0.12	625	10×20	0.30	820	10×25	0.12	950			
220	10×16	0.09	770	10×25	0.20	1040	12.5×20	0.085	1140			
330	10×20	0.060	1060	12.5×20	0.12	1281	12.5×25	0.060	1420			
470	12.5×20	0.046	1401	12.5×25	0.085	1500	16×25	0.055	1700			
680	12.5×25	0.036	1660	16×20	0.060	1630	16×31.5	0.032	2050			
1000	16×20	0.034	1770	16×31.5	0.040	2120	18×35.5	0.029	2280			
1500	16×31.5	0.028	2385	16×40	0.035	2410						
2200	16×35.5	0.020	2680	18×40	0.030	2560						
3300	18×40	0.017	3040									