



Schematic



PANEL MOUNTING



SPECIFICATIONS:

CONTACT RATING : 5 AMPS @ 120 V AC or 28 V DC.
 2 AMPS @ 250 V AC or 0.4VA AMPS @20 V AC or DC.
 ELECTRICAL LIFE : 6,000 make-and-break cycles at full load.
 CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 V DC.
 100 mA, for both silver and gold plated contacts.
 INSULATION RESISTANCE : 1,000 MΩ min.
 DIELECTRIC STRENGTH : 1,000 V RMS @ sea level.
 OPERATING TEMPERATURE : -30 °C to 130 °C

MATERIALS:

CASE : Diallyl phthalate (DAP)(UL-94V-0).
 ACTUATOR : Nylon, black standard.
 BUSHING : ZINC ALLOY.
 HOUSING : Stainless steel.
 TERMINAL/CONTACT : Copper alloy, with silver or gold plated.
 or gold over silver.
 SWITCH SUPPORT : Brass, tin plated.

NOTE: TOLERANCES UNLESS OTHERWISE SPECIFIED : + .012 (mm).
 0.3

REVISION	DESCRIPTION	REVISED BY	TOLERANCES .X .XX		ANGLE 1/2'	⊕	◁	UNIT	mm	PART NAME	SPEC DRAWING	DWG NO
△			DRAWN BY	張俊雄	DESIGNED BY	王豐文	SCALE			PART NO		WS2370A
△			CHECKED BY	Jimmy	APPROVED BY		DATE	2014.01.17				
△	2014.01.17 首次出圖	張俊雄								PART NO	A2R30-R04#E	