

Installation:

* Insulation: Nylon 66, Color Nature

Ordering Code:


CP-01 1 ** 0 * 0
① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Contact Type: 1= Receptacle
- ③ No of Circuits:
- ④ Plating Code: 0= Non plating
- ⑤ Variation:
6= UL 94V-2, B.M.I type
7= UL 94V-0, B.M.I type
- ⑥ Other options: 0= Standard

| Circuits | Dimension | | | | |
|----------|--------------|-------------|--------------|-------------|-------------|
| | A | B | C | D | E |
| 4 | 4.20(.165) | 40.4(1.591) | 29.2(1.150) | 9.7(.382) | 12.8(.504) |
| 6 | 8.40(.331) | 44.6(1.756) | 33.40(1.315) | 13.9(.547) | 17.0(.669) |
| ⚠ 8 | 12.60(.496) | 48.8(1.921) | 37.60(1.480) | 18.1(.713) | 21.2(.835) |
| 10 | 16.80(.661) | 53.0(2.087) | 41.80(1.646) | 22.3(.878) | 25.4(1.000) |
| 14 | 25.20(.992) | 61.4(2.417) | 50.20(1.976) | 30.7(1.209) | 33.8(1.331) |
| 18 | 33.60(1.323) | 69.8(2.748) | 58.60(2.307) | 39.1(1.539) | 42.2(1.661) |
| 24 | 46.20(1.819) | 82.4(3.244) | 71.20(2.803) | 51.7(2.035) | 54.8(2.157) |

Halogen-Free

RoHS Compliant

| | | | | | | | | |
|-----|-------|----------|------------|--|-----------------------------|--------------------------------------|--|--|
| ④ | | | | | DATE | UNIT: mm / inch | TITLE: 4.20mm PICH BMI TYPE RECEPTACLE CONN. |  瀚荃股份有限公司 CviLux Corporation |
| ③ | | | | | DRAWN BY: Karen 10/4-13' | TOLERANCE UNLESS OTHERWISE SPECIFIED | MATERIAL: | |
| ② | | | | | ENGINEER: Easley 10/4-13' | .X ± 0.38/.015 X' ± 1' | FINISH: | |
| ① | Karen | 10/4-13' | ECNT113068 | | CHECKED BY: Easley 10/4-13' | .XX ± 0.25/.010 .X' ± | | |
| SYM | NAME | DATE | REVISIONS | | APPROVED BY: David 10/4-13' | .XXX ± 0.10/.004 .XX' ± | | DRAWING NO. CP0134SE PART NO. CP-011**0*0 |
| | | | | | | | | SCALE 2 / 1 SHEET 1 OF 1 |

