



REV	EC.N NO.	CONTENT	CHK	DATE
V0.0		初版	ZCP	2016.11.24

NOTES:

- Rating: <UL> 300V/10A  
<IEC> 250V/10.5A
- Poles:03P
- Insulation Withstands Voltage: AC2000V/1 Min
- Insulation Resistance: 500MΩ at DC500V
- Using Temperature Range: -40°C/+115°C
- Max soldering : +250° for 5S
- Rohs Compliance.
- Suitable Electric Wire:28-18AWG(UL) 0.2-1.0mm² (IEC)
- With" ★ "is important dimension

How to order  
**UL0-TB12 - 250B/3.5 - 08P - 1 0 0 QA**

Certificate Factory poles color: Customer requirements  
 Series NO. Code 1:Grey 2:Blue 3:Black 4:Green 5:Orange 6:Red 7:transparent 8:Yellow 9:White

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
5	SHORT-PIN	3001B0020	1	Phosphor bronze	Tin Plated
4	LONG-PIN	3001B0010	2	Phosphor bronze	Tin Plated
3	LEVER	3001D0Y00A	3	PA66	UL94V-0
2	Cover	3001C0Y00A	1	PA66	UL94V-0
1	Housing	3001A0YXXA	3	PA66	UL94V-0

  

DWG	ZCP	DATE	16.11.24	UNITS	MM	SHEET/OF	1/1
CHK		DATE		SCALE	1:1	A4	
APP		DATE					

  

NAME	DWGNO
<b>UL0-TB12-250B/3.5-08P-100QA</b>	UL0TB12Y000A

NINGBO UL0 ELECTRONICS CO.,LTD.

REV:1.0



NINGBO UL0 ELECTRONICS CO.,LTD.  
 宁波欧路电子有限公司