



线数	编号	尺寸Dimensions (mm)			
Poles	Part No	A	B	C	D
1	FL-1A	0	0	5.6	5.6
2	FL-2A	4.14	0	9.8	5.6
3	FL-3A	8.28	0	14.0	5.6
4	FL-4A	4.14	4.14	9.8	9.8
6	FL-6A	4.14	8.28	9.8	14.0
9	FL-9A	8.28	8.28	14.0	14.0
12	FL-12A	8.28	12.42	14.0	18.2
15	FL-15A	8.28	16.56	14.0	22.4

■ 技术参数 (SPECIFICATIONS)

- ◆ 额定电压: 300V AC DC
Voltage rating: 300V AC DC
- ◆ 额定电流: 10~8.0A AC DC MIN
Current rating: 10~8.0A AC DC MIN
- ◆ 耐压值: 1500V AC/minute
Withstand voltage: 1500V AC/minute
- ◆ 绝缘电阻: 1000MΩ MIN
Insulation resistance: 1000MΩ MIN
- ◆ 接触电阻: 20mΩ MAX
Contact resistance: 20mΩ MAX
- ◆ 工作温度: -25°C ~+85°C
Working Temperature: -25°C ~+85°C
- ◆ 间距: 4.14 mm
Pitch: 4.14 mm

■ 材料 (MATERIAL)

- ◆ 外壳: 尼龙66
Housing: Nylon66

GENERAL TOLERANCE		SCALE	DRAWIN	DATE	DWG. NO.	TITLT.	REV.
XX. ±0.25	XXX. ±0.40	UNIT mm	CHECK	DATE	FL	成品图	A
X. ±0.20	.XXX ±0.05		APPROVE	DATE	PARTS NO.		SHEET.
.X ±0.15	X.° ±2°	SIZE A4			HR4141A-nY (FL-nA)		1/1
.XX ±0.10	.X° ±1°						